

*Specialists in
Safety
Identification
Products*

Harris West
5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East
181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Technical Specifications

FLAGGING TAPE

DESCRIPTION:

Our non-adhesive flagging tape is excellent for marking hazards, trees, danger areas, and flagging survey markers and boundaries. Available in 2-mil solids and 4-mil fluorescent colors.

TECHNICAL DATA:

Thickness:	2 mil to 4 mil.
Tolerance:	+/- 1.5%
Specific Gravity:	1.28 to 1.40 GR/CC ASTM-D-792
Embossing Pattern:	Taffeta
Process Type:	Flexible PVC Film, Monomeric
Width:	1 1/8"
Core Sizes:	1 1/2"
100% Modulus, PSI:	1370 to 1820
Tensile, PSI:	2620 to 2990
Elongation (%):	265 to 295
Brittleness, Deg. F.	0 to -40
Footage:	
Standard Colors	300'
Fluorescent Colors	150'
Embossed Gauges:	
Standard Roll Flag:	2.50 +/- 0.50 mil
Fluor. Roll Flag:	2.50 +/- 0.50 mil