

*Specialists in
Safety
Identification
Products*

Harris West
5181 Argosy Avenue
Huntington Beach, CA 92649

Phone:
(714) 898-8048
(800) 222-6866

Fax:
(714) 898-7108
(800) 228-1274

Harris East
181 Conant Drive
Pawtucket, RI 02860

Phone:
(401) 727-3160
(800) 443-2821

Fax:
(401) 727-3162

Technical Specifications

DOUBLE COATED FOAM MOUNTING TAPE

DESCRIPTION:

Tape is 1/32" white cross linked polyethylene foam coated on both sides with a high performance rubber-base adhesive. Tape is designed for general purpose mounting applications to high and low surface energy substrates. Tape is coated with a high performance solvent based rubber which exhibits a good balance of tack, peel adhesion and shear. Tape is not recommended for applications where direct exposure to UV light is required.

SPECIFICATIONS:

Adhesive:	1.5 mils +/- 10% on liner side 1.5 mils +/- 10% on unwind side
Carrier:	1/32", 6 lb. density white XL-PE foam
Liner:	60 lb. bleached densified kraft

PERFORMANCE DATA:

Peel Adhesion:	15 minute applied, ounces/inch foam tear
	24 hour applied, ounces/inch foam tear
Shear Adhesion:	1/2" x 1/2", 1,000 grams +100 hours
Minimum Application Temp.:	+50 degrees F
No Load Applied, Service Temperature Range:	-20 to 130 degrees F Continuous -20 to 160 degrees F Short Term

NOTE: Performance data indicates average production values from stainless steel and should not be used for minimum specification values. It is required that the converter determines suitability of tape prior to use.

The information contained herein, is to the best of our knowledge and belief, accurate. However, since the conditions of handling and of use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by following these suggestions. Nothing contained herein is to be construed as a recommendation for use in violation of any patents or of applicable laws or regulations.