

Specialists in
Safety
Identification
Products

Harris West

5181 Argosy Avenue Huntington Beach, CA 92649

> Phone: (714) 898-8048 (800) 222-6866

Fax: (714) 898-7108 (800) 228-1274

Harris East

181 Conant Drive Pawtucket, RI 02860

> Phone: (401) 727-3160 (800) 443-2821

Fax: (401) 727-3162

Technical Specifications

ECONOMY HAZARD WARNING TAPE

APPLICATION:

Designed expressly for safety marking applications in industrial plants, commercial buildings, institutions and recreational facilities. Used to mark obstructions, low hanging objects, pillars, handrails, passageways, aisles and any potentially hazardous areas or objects.

FEATURES / BENEFITS:

- Can be applied quickly and easily; requires minor surface preparation, with no time consuming scraping and cleaning necessary.
- No downtime required for drying after installation.

COLORS:

Yellow/Black, White/Red, White/Green, White/Black

TECHNICAL DATA:

Backing Material: Plasticized PVC

Adhesive: Rubber Based Adhesive

Total Tape Thickness: 6 mil; 0.17 mm

Tensile Strength (N/cm): 23N/cm
Elongation at Break (%): 170%
Peel Adhesion (N/cm): 1.2N/cm
Unwinding force (N/cm): 2.3 N/cm

Temperature Resistance (°C): -10°C -- +80°C Shelf Life (month) 12 months

Note: The above are typical values and should not be used in writing specifications.